

## iD-HP Series Loudspeakers



The inDESIGN iD-HP loudspeaker series is a compact, high output design suitable for mobile and permanent sound installations.

Attention to detail during development of these products provides high SPL output with a smooth neutral sonic character, multiple installation options at a very competitive price.

All mid-high models are fitted with a NEAR / FAR switch. This feature allows users to change the sonic footprint depending on the listening scenario.

Users may use these products in vertical or horizontal orientations – just rotate the horn!

All models are shipped with a U-bracket and are available in black and white colour.

MODEL	iD-HP108 / iD-HP108 W	iD-HP110 / iD-HP110 W	iD-HP112 / iD-HP112 W	iD-HP15SUB / iD-HP15SUB W	iD-HP18SUB / iD-HP18SUB W
Design	2-way passive			Front-loaded bass reflex	
Frequency response -3dB	60Hz - 18kHz	55Hz - 18kHz	50Hz - 18kHz	40Hz - 300Hz	45Hz - 300Hz
Frequency response -10dB	55Hz - 20kHz	50Hz - 20kHz	45Hz - 20kHz		
LF driver woofer	1x 8" (200mm) 2" voice coil	1x 10" (250mm) 2.5" voice coil	1x 12" (300mm) 3" voice coil	1x 15" (385mm) 4" voice coil	1x 18" (460mm) 4" voice coil
HF driver compression driver	1x 1" (25mm) 1" voice coil	1x 1" (25mm) 1.7" voice coil			
Rated power watts	150W RMS, 600W peak	250W RMS, 1000W peak	300W RMS, 1200W peak	600W RMS, 2400W peak	
Sensitivity	93dB 1W/1m	95dB 1W/1m	97dB 1W/1m	99dB 1W/1m	100dB 1W/1m
Max SPL	115dB continuous, 121dB peak	119dB continuous, 125dB peak	122dB continuous, 128dB peak	126dB continuous, 132dB peak	128dB continuous, 134dB peak
Impedance	8Ω nominal				
Dispersion -6dB	90 x 50 (Rotatable Horn)	90 x 50 (Rotatable Horn)	90 x 40 (Rotatable Horn)		
Crossover frequency	2.8kHz passive	2.0kHz passive	2.0kHz passive		
Input connectors	2x NL4 Speakon				
Cabinet construction	Plywood				
Top hat	Yes (35mm)				
Eye bolt mounting	Yes – refer to manual. M8 (1.25) x 40mm			No. Ground stack only.	
Black colour	Yes				
White colour	Yes				
Shipping dimensions	330 x 310 x 520 mm	388 x 398 x 570 mm	454 x 454 x 715mm	670 x 550 x 605mm	880 x 660 x 655mm
Shipping weight	12kg	18kg	25kg	34kg	38kg
Included accessories	U-mount bracket				

Description and specifications are correct at time of printing. Maybe subject to change without notice.