

iD-SMA50 Active Two Way Stereo Speaker System



The inDESIGN iD-SMA50 is an active two-way stereo speaker system consisting of one powered and one passive speaker.

The speakers are compact, architecturally pleasing and come supplied with adjustable mounting brackets.

Features include AUTO standby, an on-board 25W stereo amplifier, Treble, Bass and Volume controls as well as unbalanced stereo RCA and balanced stereo inputs.

The iD-SMA50 features a 5.25" bass driver, a 1" piezo high frequency tweeter delivering a solid 2 x 25 watts RMS of clear, intelligible power.

The inDESIGN iD-SMA50 powered speakers deliver a new standard of high quality sound reinforcement for a variety of audio and visual applications. Compact and well designed, they are easy to operate and are set to become the standard in many AV installations. The speakers are available in white (iDSMA50-W) and black (iD-SMA50-B) variants.

MODEL	iD-SMA50-B / iD-SMA50-W
SPEAKER SYSTEM	2 WAY ACTIVE SPEAKER, 2 WAY PASSIVE SPEAKER
Power (Continuous)	2x 25 Watts
Auto Standby/Sleep Function	Auto Standby/Sleep Function
Impedance	8 ohm
Sensitivity	89dB
Calculated Max. SPL (Per Speaker)	100dB
Frequency Response (-3 dB)	45Hz-20kHz
Frequency Response (-10 dB)	40Hz-22kHz
Speaker Components	Woofer: 133mm (5.25") Polypropylene Tweeter: 25mm (1") Piezo
Dispersion -6dB (H x V)	60 x 90
Mains Power Requirement	230VAC, 50Hz, 50W
Each Speaker Dimension (W x H x D)	163 x 252 x 163 mm (6.5" x 10" x 6.5")
Box (Pair) Dimensions (W x H x D)	420 x 275 x 195 mm (16.5" x 10.8" x 7.7")
Weight	Active Speaker: 3kg (6.6lbs) Passive Speaker: 2kg (4.4lbs)
Gross Weight per Pair (Box)	6.8kg (13.4lbs)
Accessories (Supplied)	Active Speaker Passive Speaker Wall Brackets (Pair) 3 metre Speaker Cable 1.5 metre Main Cord Instruction Manual Remote Control!
Shipping Weight	5.5kg

Description and specifications are correct at time of printing. Maybe subject to change without notice.

FREQUENCY RESPONSE & POLAR PLOT DIAGRAMS

